

Description

length: 1.698", grip: 1.375", thread: 10-32, hex head - drilled shank - tension - short thread - cadmium plated alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS620322D |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5306-01-442-7555 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS6203-22D Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.323 Inches Nominal |
| Fastener Length: | 1.683 Inches Minimum And 1.713 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.110 Inches Minimum And 0.125 Inches Maximum |
| Width Between Flats: | 0.367 Inches Minimum And 0.376 Inches Maximum |
| Grip Diameter: | 0.1885 Inches Minimum And 0.1895 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.070 Inches Minimum Threads And 0.080 Inches Maximum Threads |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 1.365 Inches Minimum And 1.385 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 0.168 Inches Nominal Threads |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Steel Comp 4340 Overall Or Steel Comp 8740 Overall |
| Material Document And Classification: | Mil-s-5000 Mil Spec 1st Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416, Type 2, Class 2 Fed Spec All Treatment Responses Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas6203 Professional/industrial Association Standard |

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6203-22D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.