

**Description**

length: 2.698", grip: 2.375", thread: 10-32, hex head, tension, short thread, cadmium plated alloy steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS620338                                 |
| Minimum Qty (MOQ):      | 5   |
| NSN:                    | 5306-01-183-3322                          |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N NAS6203-38 Specifications

|                                     |   |
|-------------------------------------|---|
| <b>Thread Class:</b>                | 3a  |
| <b>Thread Direction:</b>            | Right-hand  |
| <b>Thread Length:</b>               | 0.323 Inches Nominal  |
| <b>Fastener Length:</b>             | 2.698 Inches Nominal  |
| <b>Head Style:</b>                  | Dished Hexagon  |
| <b>Head Height:</b>                 | 0.110 Inches Minimum And 0.125 Inches Maximum                       |
| <b>Width Between Flats:</b>         | 0.367 Inches Minimum And 0.376 Inches Maximum                       |
| <b>Grip Diameter:</b>               | 0.1810 Inches Minimum And 0.1840 Inches Maximum                     |
| <b>Nominal Thread Diameter:</b>     | 0.190 Inches  |
| <b>Grip Length:</b>                 | 2.375 Inches Nominal  |
| <b>Thread Quantity Per Inch:</b>    | 32  |
| <b>Minimum Tensile Strength:</b>    | 160000 Pounds Per Square Inch                                       |
| <b>Hardness Rating:</b>             | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| <b>Material:</b>                    | Steel Overall   |
| <b>Surface Treatment:</b>           | Cadmium Overall And Chromate Overall                                |
| <b>Thread Series Designator:</b>    | Unjf  |
| <b>Specification/standard Data:</b> | 80205-nas6203 Professional/industrial Association Standard          |

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6203-38> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.