

**Description**

length: 0.573", grip: 0.250", thread: 10-32, hex head, drilled shank, tension, short thread, cadmium plated alloy steel, NAS6203 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS62034D
Minimum Qty (MOQ):	25
NSN:	5306-01-334-6327
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N NAS6203-4D Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.323 Inches Nominal
<b>Fastener Length:</b>	0.558 Inches Minimum And 0.588 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.110 Inches Minimum And 0.125 Inches Maximum
<b>Width Between Flats:</b>	0.372 Inches Nominal
<b>Grip Diameter:</b>	0.1885 Inches Minimum And 0.1895 Inches Maximum
<b>Shank Unthreaded Hole Diameter:</b>	0.070 Inches Minimum First Hole And 0.080 Inches Maximum First Hole
<b>End Item Identification:</b>	Pacer Dawn
<b>Nominal Thread Diameter:</b>	0.1900 Inches
<b>Grip Length:</b>	0.240 Inches Minimum And 0.260 Inches Maximum
<b>Thread Quantity Per Inch:</b>	32
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	0.409 Inches Nominal First Hole
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6203-4D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.