

Description

length: 0.635", grip: 0.312", thread: 10-32 - oversized hex head - tension - short thread - cadmium plated alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS62035X
Minimum Qty (MOQ):	5
NSN:	5306-01-147-4883
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS6203-5X Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.298 Inches Minimum And 0.348 Inches Maximum
Fastener Length:	0.620 Inches Minimum And 0.650 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.110 Inches Minimum And 0.125 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Shoulder Diameter:	0.2016 Inches Minimum First Shoulder And 0.2026 Inches Maximum First Shoulder
Shoulder Length:	0.302 Inches Minimum First Shoulder And 0.322 Inches Maximum First Shoulder
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Shoulder Shape:	Round First Shoulder
Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Type 2 Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6203 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6203-5X> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.