

Description

NAS6204-11Y Shoulder Bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS620411Y
Minimum Qty (MOQ):	5
NSN:	5306-01-303-7391
ECCN:	EAR99



* See page 2 for technical characteristics

P/N NAS6204-11Y Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.345 Inches Minimum And 0.395 Inches Maximum
Fastener Length:	1.043 Inches Minimum And 1.073 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.429 Inches Minimum And 0.439 Inches Maximum
Shoulder Diameter:	0.2797 Inches Minimum First Shoulder And 0.2807 Inches Maximum First Shoulder
Shoulder Length:	0.678 Inches Minimum First Shoulder And 0.698 Inches Maximum First Shoulder
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Shoulder Shape:	Round First Shoulder
Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this shoulder bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shoulder+bolts/NAS6204-11Y> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.