

Description

NAS6204-13X Shear Bolt

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | NAS620413X |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5306-01-259-1184 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



NO IMAGE
AVAILABLE

P/N NAS6204-13X Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.370 Inches Nominal |
| Fastener Length: | 1.251 Inches Minimum And 1.281 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.125 Inches Minimum And 0.140 Inches Maximum |
| Width Between Flats: | 0.429 Inches Minimum And 0.439 Inches Maximum |
| Grip Diameter: | 0.2641 Inches Minimum And 0.2651 Inches Maximum |
| Nominal Thread Diameter: | 0.2500 Inches |
| Grip Length: | 0.802 Inches Minimum And 0.822 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| Material: | Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Ty2 Cl2 Fed Spec 1st Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas6204 Professional/industrial Association Standard |

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6204-13X> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.