

Description

length: 1.308", grip: 0.938", thread: 1/4-28, hex head, drilled shank, tension, short thread, cadmium plated alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS620415D
Minimum Qty (MOQ):	20
NSN:	5306-01-142-2126
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS6204-15D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.370 Inches Nominal
Fastener Length:	1.308 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.132 Inches Nominal
Width Between Flats:	0.434 Inches Nominal
Grip Diameter:	0.2490 Inches Nominal
Shank Unthreaded Hole Diameter:	0.081 Inches Nominal First Hole
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.938 Inches Nominal
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.138 Inches Nominal First Hole
Material:	Steel Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6204 Professional/Industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6204-15D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.