

Description

length: 1.432", grip: 1.062", thread: 1/4-28, close tolerance, drilled shank

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS620417D |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5306-01-143-3989 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N NAS6204-17D Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.370 Inches Nominal |
| Fastener Length: | 1.432 Inches Nominal |
| Head Style: | Dished Hexagon |
| Head Height: | 0.132 Inches Nominal |
| Width Between Flats: | 0.434 Inches Nominal |
| Grip Diameter: | 0.2490 Inches Nominal |
| Shank Unthreaded Hole Diameter: | 0.081 Inches Nominal First Hole |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 1.062 Inches Nominal |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 1.262 Inches Nominal First Hole |
| Material: | Steel Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas6204 Professional/Industrial Association Standard |

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6204-17D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.