



★ FASTENERS

Military-Fasteners.com

P/N NAS6204-26D

## Description

length: 1.995", grip: 1.625", thread: 1/4-28, hex head, drilled shank, tension, short thread, cadmium plated alloy steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS620426D
Minimum Qty (MOQ):	10
NSN:	5306-01-142-2139
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N NAS6204-26D Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.370 Inches Nominal
<b>Fastener Length:</b>	1.995 Inches Nominal
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.132 Inches Nominal
<b>Width Between Flats:</b>	0.434 Inches Nominal
<b>Grip Diameter:</b>	0.2490 Inches Nominal
<b>Shank Unthreaded Hole Diameter:</b>	0.081 Inches Nominal First Hole
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Grip Length:</b>	1.625 Inches Nominal
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	1.825 Inches Nominal First Hole
<b>Material:</b>	Steel Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas6204 Professional/industrial Association Standard

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6204-26D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.