

## P/N NAS6204-29H

### **Description**

Fastener Length: 2-3/16", Hole Diameter: 3/64", Thread: 1/4-28, Thread Length: 25/64"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	NAS620429H
Minimum Qty (MOQ):	1
NSN:	5306-01-290-9677
National Motor Freight	093486 Bolts nuts Or Screws Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS6204-29H Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.345 Inches Minimum And 0.395 Inches Maximum
Fastener Length:	2.167 Inches Minimum And 2.197 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.429 Inches Minimum And 0.439 Inches Maximum
Hole Diameter:	0.046 Inches Minimum And 0.056 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	1.802 Inches Minimum And 1.822 Inches Maximum
Hole Quantity:	3
Hole Type:	Drilled
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	40.0 Rockwell C Minimum Overall And 46.0 Rockwell C Maximum Overall
Hole Configuration Style:	Hexagon Corners
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6204 Professional/industrial Association Standard

# **How to Order**

