

**Description**

length: 2.308", grip: 1.938", thread: 1/4-28, hex head, tension, short thread, cadmium plated alloy steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS620431
Minimum Qty (MOQ):	25
NSN:	5306-01-475-5197
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N NAS6204-31 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.370 Inches Nominal
<b>Fastener Length:</b>	2.308 Inches Nominal
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.125 Inches Minimum And 0.140 Inches Maximum
<b>Width Between Flats:</b>	0.429 Inches Minimum And 0.439 Inches Maximum
<b>Grip Diameter:</b>	0.2445 Inches Minimum And 0.2450 Inches Maximum
<b>End Item Identification:</b>	Fixed Wing Aircraft, C130j Hercules, Lockheed Martin Corp
<b>Nominal Thread Diameter:</b>	0.375 Inches
<b>Grip Length:</b>	1.938 Inches Nominal
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	180000 Pounds Per Square Inch
<b>Material:</b>	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6204-31> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.