

Description

length: 2.433", grip: 2.063", thread: 1/4-28, hex head, tension, short thread, cadmium plated alloy steel, NAS6204 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS620433 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5306-01-176-1988 |
| Schedule B: | 7318.15.2095 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS6204-33 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.370 Inches Nominal |
| Fastener Length: | 2.417 Inches Minimum And 2.447 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.125 Inches Minimum And 0.140 Inches Maximum |
| Width Between Flats: | 0.429 Inches Minimum And 0.439 Inches Maximum |
| Grip Diameter: | 0.2485 Inches Minimum And 0.2495 Inches Maximum |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 2.052 Inches Minimum And 2.072 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| Material: | Steel Overall |
| Material Document And Classification: | Mil-s-5000,4340 Or E4340 Mil Spec Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas6204 Professional/industrial Association Standard |

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6204-33> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.