

Description

length: 2.682", grip: 2.312", thread: 1/4-28, hex head, tension, short thread, cadmium plated alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS620437 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5306-01-347-2020 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N NAS6204-37 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.370 Inches Nominal |
| Fastener Length: | 2.683 Inches Nominal |
| Head Style: | Hexagon |
| Head Height: | 0.110 Inches Minimum And 0.115 Inches Maximum |
| Width Between Flats: | 0.429 Inches Minimum And 0.439 Inches Maximum |
| Grip Diameter: | 0.249 Inches Minimum And 0.250 Inches Maximum |
| End Item Identification: | Pacer Dawn |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 2.313 Inches Nominal |
| Thread Quantity Per Inch: | 28 |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,type II,class 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6204-37> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.