

P/N NAS6204-43D

Military-Fasteners.com

Description

Fastener Length: 3-1/16", Thread: 1/4-28, Thread Length: 25/64

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

| SKU / Model: | NAS620443D |
|-------------------------|---|
| Minimum Qty (MOQ): | 2 |
| NSN: | 5306-01-345-3640 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N NAS6204-43D Specifications

| За |
|--|
| Right-hand |
| 0.345 Inches Minimum And 0.395 Inches Maximum |
| 3.043 Inches Minimum And 3.073 Inches Maximum |
| Dished Hexagon |
| 0.125 Inches Minimum And 0.140 Inches Maximum |
| 0.429 Inches Minimum And 0.439 Inches Maximum |
| 0.2485 Inches Minimum And 0.2495 Inches Maximum |
| 0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole |
| 0.250 Inches |
| 2.678 Inches Minimum And 2.698 Inches Maximum |
| 28 |
| 160000 Pounds Per Square Inch |
| 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| 2.863 Inches Minimum First Hole And 2.940 Inches Maximum First Hole |
| 32.0 Microinches Bearing Surface Of Head32.0 Microinches Grip32.0 Microinches Threads |
| Steel Comp E4340 Overall Or Steel Comp 8740 Overall |
| Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall |
| Cadmium Overall And Chromate Overall |
| Qq-p-416 Ty 2,cl 2 Fed Spec Single Treatment Response Overall |
| Unjf |
| 80205-nas6204 Professional/industrial Association Standard |
| |

How to Order

Order this shear bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/shear+bolts/NAS6204-43D</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.