

# **P/N NAS6204-45D**

### **Description**

Fastener Length: 3-3/16", Thread: 1/4-28, Thread Length: 25/64"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	NAS620445D
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-505-5797
Schedule B:	7318.15.8085
FCCN:	FAR99



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS6204-45D Specifications

Thread Direction:  Thread Length:  O.345 Inches Minimum And 0.395 Inches Maximum  Fastener Length:  3.167 Inches Minimum And 3.197 Inches Maximum  Head Style:  Dished Hexagon
Fastener Length: 3.167 Inches Minimum And 3.197 Inches Maximum
Head Style: Dished Hexagon
District Horagon
Head Height: 0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats: 0.429 Inches Minimum And 0.439 Inches Maximum
Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum
Shank Unthreaded Hole Diameter: 0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
Nominal Thread Diameter: 0.250 Inches
Grip Length: 2.802 Inches Minimum And 2.822 Inches Maximum
Thread Quantity Per Inch: 28
Minimum Tensile Strength: 160000 Pounds Per Square Inch
Hardness Rating: 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Distance From Head Largest Bearing Surface To Shank Hole Center: 3.002 Inches Minimum First Hole And 3.022 Inches Maximum First Hole
Surface Finish: 32.0 Microinches Bearing Surface Of Head
Surface Finish: 32.0 Microinches Grip
Surface Finish: 32.0 Microinches Threads
Material: Steel Comp E4340 Overall
Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Overall
Surface Treatment: Cadmium Overall
Surface Treatment Document And Classification: Qq-p-416, Type 2,class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator: Unjf
Specification/standard Data: 80205-nas6204 Professional/industrial Association Standard

# **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/shear+bolts/NAS6204-45D">https://military-fasteners.com/bolts/shear+bolts/NAS6204-45D</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.