

Description

length: 3.245", grip: 2.875", thread: 1/4-28, hex head, tension, short thread, cadmium plated alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS620446
Minimum Qty (MOQ):	10
NSN:	5306-01-383-6896
ECCN:	EAR99



P/N NAS6204-46 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.370 Inches Nominal
Fastener Length:	3.230 Inches Minimum And 3.260 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.125 Inches Nominal
Width Between Flats:	0.429 Inches Nominal
Grip Diameter:	0.248 Inches Nominal
Nominal Thread Diameter:	0.250 Inches
Grip Length:	2.265 Inches Nominal
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6204-46 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6204-46> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.