

P/N NAS6204-8H

Description

Hole Diameter: 3/64", Thread: 1/4-28,

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS62048H

Minimum Qty (MOQ): 10

NSN: 5306-01-234-4734

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)







P/N NAS6204-8H Specifications

| Thread Class: | 3a |
|--|---|
| Thread Direction: | Right-hand |
| Thread Length: | 0.370 Inches Nominal |
| Fastener Length: | 0.870 Inches Nominal |
| Head Style: | Dished Hexagon |
| Head Height: | 0.133 Inches Nominal |
| Width Between Flats: | 0.434 Inches Nominal |
| Hole Diameter: | 0.046 Inches Minimum And 0.056 Inches Maximum |
| Grip Diameter: | 0.2490 Inches Nominal |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.465 Inches Nominal |
| Hole Quantity: | 3 |
| Hole Type: | Drilled |
| Thread Quantity Per Inch: | 28 |
| Hole Configuration Style: | Hexagon Corners |
| Material: | Steel Overall |
| Material Document And Classification: | Mil-s-5000 Mil Spec Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-416 Ty2 Cl2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this shear bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6204-8H and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.