

# P/N NAS6204L1

Military-Fasteners.com

#### Description

Fastener Length: 7/16", Thread: 1/4-28, Thread Length: 25/64",

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model:	NAS6204L1
Minimum Qty (MOQ):	10
NSN:	5306-01-459-2743
Schedule B:	7318.15.8085
ECCN:	9A991



## P/N NAS6204L1 Specifications

Thread Direction:   Right-hand     Thread Length:   0.345 Inches Minimum And 0.395 Inches Maximum     Fastener Length:   0.417 Inches Minimum And 0.447 Inches Maximum     Head Style:   Dished Hexagon     Head Style:   0.125 Inches Minimum And 0.140 Inches Maximum     Width Between Flats:   0.429 Inches Minimum And 0.140 Inches Maximum     Locking Feature:   0.429 Inches Minimum And 0.439 Inches Maximum     Grip Diameter:   0.2485 Inches Minimum And 0.2495 Inches Maximum     Nominal Thread Diameter:   0.2500 Inches     0.550 Inches Minimum And 0.072 Inches Maximum   Consci Inches     Minimum Tensile Strength:   0.502 Inches Minimum And 0.072 Inches Maximum     Thread Quantity Per Inch:   28     Surface Finish:   36.0 Rockwell C Minimum Fastener And 40.0 Rockwell C Maximum Fastener     Surface Finish:   32.0 Microinches Bearing Surface Of Head     Surface Finish:   32.0 Microinches Grip     Surface Finish:   32.0 Microinches Threads     Miterial:   Postic Polyamide Locking Feature     Material:   Stel Comp E4340 Fastener Or Stel Comp 8740 Fastener
Fastener Length:0.417 Inches Minimum And 0.447 Inches MaximumHead Style:Dished HexagonHead Height:0.125 Inches Minimum And 0.140 Inches MaximumWidth Between Flats:0.429 Inches Minimum And 0.439 Inches MaximumLocking Feature:Patch Threads Or Strip Threads Or Pellet ThreadsGrip Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumNominal Thread Diameter:0.2500 InchesO.052 Inches Minimum And 0.072 Inches MaximumThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Platic Polyamide Locking Feature Or Steel Comp 8740 FastenerMaterial:Neu Stat Material Response Fastener Or Steel Comp 8740 FastenerMiles-S000 Mile Seer To Steel Comp Fastener Or Miles-6049 Mile Spec 2nd Material Response Fastener Or Ams 6322 Assn
Fastener Length:0.417 Inches Minimum And 0.447 Inches MaximumHead Style:Dished HexagonHead Height:0.125 Inches Minimum And 0.140 Inches MaximumWidth Between Flats:0.429 Inches Minimum And 0.439 Inches MaximumLocking Feature:Patch Threads Or Strip Threads Or Pellet ThreadsGrip Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumNominal Thread Diameter:0.2500 InchesO.052 Inches Minimum And 0.072 Inches MaximumThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Platic Polyamide Locking Feature Or Steel Comp 8740 FastenerMaterial:Neu Stat Material Response Fastener Or Steel Comp 8740 FastenerMiles-S000 Mile Seer To Steel Comp Fastener Or Miles-6049 Mile Spec 2nd Material Response Fastener Or Ams 6322 Assn
Head Height:0.125 Inches Minimum And 0.140 Inches MaximumWidth Between Flats:0.429 Inches Minimum And 0.439 Inches MaximumLocking Feature:Patch Threads Or Strip Threads Or Pellet ThreadsGrip Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumNominal Thread Diameter:0.2500 InchesObj Diameter:0.520 InchesObj Diameter:0.521 Inches Minimum And 0.072 Inches MaximumNominal Thread Diameter:0.521 Inches Minimum And 0.072 Inches MaximumThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Fastener And 40.0 Rockwell C Maximum FastenerSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Plastic Polyamide Locking FeatureMaterial:Steel Comp E4340 Fastener Or Steel Comp 8740 FastenerMiles-5000 Mil Spec 1st Material Response Fastener Or Miles-6049 Mil Spec 2nd Material Response Fastener Or Ams 6322 Assn
Width Between Flats:0.429 Inches Minimum And 0.439 Inches MaximumLocking Feature:Patch Threads Or Strip Threads Or Pellet ThreadsGrip Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumNominal Thread Diameter:0.2500 InchesOndia Thread Diameter:0.52 Inches Minimum And 0.072 Inches MaximumNominal Thread Diameter:0.052 Inches Minimum And 0.072 Inches MaximumThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Fastener And 40.0 Rockwell C Maximum FastenerSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Delatic Polyamide Locking FeatureMaterial:Steel Comp E4340 Fastener Or Steel Comp 8740 FastenerMiti-s-5000 Mil Spec 1st Material Besponse Fastener Or Mil-s-6049 Mil Spec 2nd Material Besponse Fastener Or Ams 6322 Assn
Locking Feature:Patch Threads Or Strip Threads Or Pellet ThreadsGrip Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumNominal Thread Diameter:0.2500 InchesGrip Length:0.052 Inches Minimum And 0.072 Inches MaximumThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Fastener And 40.0 Rockwell C Maximum FastenerSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Platic Polyamide Locking FeatureMaterial:Stel Comp E4340 Fastener Or Steel Comp 8740 FastenerMill-s-5000 Mil Spec 1st Material Besponse Fastener Or Mill-s-6049 Mil Spec 2nd Material Besponse Fastener Or Mill-s-6049 Mill Spec 2nd Materi
Grip Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumNominal Thread Diameter:0.2500 InchesGrip Length:0.052 Inches Minimum And 0.072 Inches MaximumThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Fastener And 40.0 Rockwell C Maximum FastenerSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Plastic Polyamide Locking FeatureMaterial:Steel Comp E4340 Fastener Or Steel Comp 8740 FastenerMiles-5000 Mil Spec 1st Material Response Fastener Or Miles-6049 Mil Spec 2nd Material Response Fastener Or Ams 6322 Assn
Nominal Thread Diameter:0.2500 InchesGrip Length:0.052 Inches Minimum And 0.072 Inches MaximumThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Fastener And 40.0 Rockwell C Maximum FastenerSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Plastic Polyamide Locking FeatureMaterial:Steel Comp E4340 Fastener Or Steel Comp 8740 FastenerMil-s-5000 Mil Spec 1st Material Response Fastener Or Mil-s-6049 Mil Spec 2nd Material Response Fastener Or Ams 6322 Assn
Grip Length: 0.052 Inches Minimum And 0.072 Inches Maximum   Thread Quantity Per Inch: 28   Minimum Tensile Strength: 160000 Pounds Per Square Inch   Hardness Rating: 36.0 Rockwell C Minimum Fastener And 40.0 Rockwell C Maximum Fastener   Surface Finish: 32.0 Microinches Bearing Surface Of Head   Surface Finish: 32.0 Microinches Grip   Surface Finish: 32.0 Microinches Grip   Surface Finish: 32.0 Microinches Threads   Material: Plastic Polyamide Locking Feature   Material: Steel Comp E4340 Fastener Or Steel Comp 8740 Fastener   Mil-s-5000 Mil Spec 1st Material Besponse Fastener Or Mil-s-6049 Mil Spec 2nd Material Besponse Fastener Or Ams 6322 Assn
Thread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Fastener And 40.0 Rockwell C Maximum FastenerSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Plastic Polyamide Locking FeatureMaterial:Steel Comp E4340 Fastener Or Steel Comp 8740 FastenerMil-s-5000 Mil Spec 1st Material Besponse Fastener Or Mil-s-6049 Mil Spec 2nd Material Besponse Fastener Or Ams 6322 Assn
Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Fastener And 40.0 Rockwell C Maximum FastenerSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Plastic Polyamide Locking FeatureMaterial:Steel Comp E4340 Fastener Or Steel Comp 8740 FastenerMil-s-5000 Mil Spec 1st Material Response Fastener Or Mil-s-6049 Mil Spec 2nd Material Response Fastener Or Ams 6322 Assn
Hardness Rating:36.0 Rockwell C Minimum Fastener And 40.0 Rockwell C Maximum FastenerSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsBaterial:Plastic Polyamide Locking FeatureMaterial:Steel Comp E4340 Fastener Or Steel Comp 8740 FastenerMil-s-5000 Mil Spec 1st Material Response Fastener Or Mil-s-6049 Mil Spec 2nd Material Response Fastener Or Ams 6322 Assn
Surface Finish: 32.0 Microinches Bearing Surface Of Head   Surface Finish: 32.0 Microinches Grip   Surface Finish: 32.0 Microinches Threads   Material: Plastic Polyamide Locking Feature   Material: Steel Comp E4340 Fastener Or Steel Comp 8740 Fastener   Mil-s-5000 Mil Spec 1st Material Response Fastener Or Mil-s-6049 Mil Spec 2nd Material Response Fastener Or Ams 6322 Assn
Surface Finish: 32.0 Microinches Grip   Surface Finish: 32.0 Microinches Threads   Material: Plastic Polyamide Locking Feature   Material: Steel Comp E4340 Fastener Or Steel Comp 8740 Fastener   Mil-s-5000 Mil Spec 1st Material Response Fastener Or Mil-s-6049 Mil Spec 2nd Material Response Fastener Or Ams 6322 Assn
Surface Finish: 32.0 Microinches Threads   Material: Plastic Polyamide Locking Feature   Material: Steel Comp E4340 Fastener Or Steel Comp 8740 Fastener   Mil-s-5000 Mil Spec 1st Material Response Fastener Or Mil-s-6049 Mil Spec 2nd Material Response Fastener Or Ams 6322 Assn
Material: Plastic Polyamide Locking Feature   Material: Steel Comp E4340 Fastener Or Steel Comp 8740 Fastener   Mil-s-5000 Mil Spec 1st Material Response Fastener Or Mil-s-6049 Mil Spec 2nd Material Response Fastener Or Ams 6322 Assn
Material: Steel Comp E4340 Fastener Or Steel Comp 8740 Fastener   Mil-s-5000 Mil Spec 1st Material Response Fastener Or Mil-s-6049 Mil Spec 2nd Material Response Fastener Or Ams 6322 Assn
Mil-s-5000 Mil Spec 1st Material Response Fastener Or Mil-s-6049 Mil Spec 2nd Material Response Fastener Or Ams 6322 Assn
Material Decument And Classification Mil-s-5000 Mil Spec 1st Material Response Fastener Or Mil-s-6049 Mil Spec 2nd Material Response Fastener Or Ams 6322 Assn
Std 2nd Material Response Fastener
Surface Treatment: Cadmium Fastener And Chromate Fastener
Surface Treatment Document And Classification: Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Fastener
Thread Series Designator: Unjf
Specification/standard Data: 80205-nas6204 Professional/industrial Association Standard

## How to Order

Order this shear bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/shear+bolts/NAS6204L1</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.