

P/N NAS6204L10

Military-Fasteners.com

Description

Fastener Length: 0-63/64", Thread: 1/4-28, Thread Length: 25/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS6204L10
Minimum Qty (MOQ):	15 EA
NSN:	5306-01-285-2747
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS6204L10 Specifications

Inread Lass:3aThread Line:Right-handThread Length:0.345 Inches Minimum And 0.395 Inches MaximumFastener Length:0.980 Inches Minimum And 1.010 Inches MaximumHead Style:Dished HexagonHead Height:0.125 Inches Minimum And 0.149 Inches MaximumWidth Between Flats:0.429 Inches Minimum And 0.439 Inches MaximumOrip Diameter:0.429 Inches Minimum And 0.439 Inches MaximumNominal Thread Diameter:0.250 InchesOf:p Length:0.515 Inches Minimum And 0.635 Inches MaximumNominal Thread Diameter:0.250 InchesOf:p Length:0.6100 Pounds Per Square InchHardness Rating:28Surface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripMaterial:Pastic Polyamide Locking FeatureMaterial:Steel Comp E4340 Fastener Or Steel Comp 8740 FastenerMaterial:Cadimi Mastener And Chorage Fastener Or Mile-s6049 Mil Spec 2nd Material Response Fastener Or Mile-So499 Mil Spec 2nd Material Response FastenerSurface Treatment:Cadimi Mastener And Chorage FastenerSurface Treatment Document AndQ-p-416.type 2.class 2 Fed Spec Single Treatment Response FastenerSurface Treatment Document And PastenUnifSurface Treatment Document And PastenerUnifSurface Treatment Document And PastenerUnifSurface Treatment Document And PastenerUnifSurface Treatment Document And PastenerUnifSurface Treatment Document And P		
Thread Length:0.345 Inches Minimum And 0.395 Inches MaximumFastener Length:0.980 Inches Minimum And 1.010 Inches MaximumHead Style:Dished HexagonHead Style:0.125 Inches Minimum And 0.140 Inches MaximumWidth Between Flats:0.429 Inches Minimum And 0.439 Inches MaximumGrip Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumNominal Thread Diameter:0.250 Inches0.429 Inches Minimum And 0.635 Inches MaximumNominal Thread Diameter:0.615 Inches Minimum And 0.635 Inches MaximumThread Quartity Per Inch:8Minimum Tensile Strength:160000 Pounds Per Square InchMarciae Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Stel Comp E4340 Fastener Or Steel Comp 8740 FastenerMaterial:Stel Comp E4340 Fastener Or Steel Comp 8740 FastenerMaterial:Scolo Mil Spec 1st Material Response Fastener Or Mil-s-6049 Mil Spec 2nd Material Response Fastener Or Ams6322 Assn St nd Material Response FastenerSurface Treatment:Cadium Fastener And Chromate FastenerSurface Treatment:Cadium Fastener And Chromate FastenerSurface Treatment:Gaq-e116,type 2,class 2 Fed Spec Single Treatment Response FastenerSurface Treatment:Unif	Thread Class:	За
Fastener Length:0.980 Inches Minimum And 1.010 Inches MaximumHead Style:Dished HexagonHead Height:0.125 Inches Minimum And 0.140 Inches MaximumWidth Between Flats:0.429 Inches Minimum And 0.439 Inches MaximumOrip Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumNominal Thread Diameter:0.250 InchesOrip Length:0.515 Inches Minimum And 0.635 Inches MaximumThread Quantity Per Inch:28Binimum Tensile Strength:16000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Fastener And 40.0 Rockwell C Maximum FastenerSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GraipSurface Finish:32.0 Microinches GraipMaterial:Palstic Polyamide Locking FeatureMaterial:Steel Comp E4340 Fastener Or Steel Comp 8740 FastenerSurface Treatment:Cadmium Fastener And Chomate Fastener Or Mil-s-6049 Mil Spec 2nd Material Response Fastener Or Ams6322 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 2nd Material Response Fastener Or Ams6322 Assn Std 2nd Material Response FastenerSurface Treatment:Cadmium Fastener And Chomate FastenerSurface Treatment Document And Classification:Qu-states Z Fed Spec Single Treatment Response FastenerThread Series Designator:Unjf	Thread Direction:	Right-hand
Head Style:Dished HexagonHead Height:0.125 Inches Minimum And 0.140 Inches MaximumWidth Between Flats:0.429 Inches Minimum And 0.439 Inches MaximumGrip Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumNominal Thread Diameter:0.250 InchesGrip Length:0.615 Inches Minimum And 0.635 Inches MaximumThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Fastener And 40.0 Rockwell C Maximum FastenerSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripMaterial:Pastic Polyamide Locking FeatureMaterial:19.300 Mil Spec 1st Material Response Fastener Or Mil-s-6049 Mil Spec 2nd Material Response Fastener Or Ams6322 Assn Std 2nd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment:Cadmium Chromate FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment:Unjf	Thread Length:	0.345 Inches Minimum And 0.395 Inches Maximum
Head Height:0.125 Inches Minimum And 0.140 Inches MaximumWidth Between Flats:0.429 Inches Minimum And 0.439 Inches MaximumGrip Dameter:0.2485 Inches Minimum And 0.2495 Inches MaximumNominal Thread Diameter:0.250 InchesGrip Length:0.615 Inches Minimum And 0.635 Inches MaximumThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchBiomage Strength:36.00 Rockwell C Minimum Fastener And 40.0 Rockwell C Maximum FastenerSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Plastic Polyamide Locking FeatureMaterial:Steel Comp E4340 Fastener Or Steel Comp 8740 Fastener Of Mil-s-6049 Mil Spec 2nd Material Response Fastener Of Mil-s-6049 Mil Spec 2nd Material Response Fastener Of And Material Response Fastener Of Mil-s-6049 Mil Spec 2nd Material Response Fastener Of And Steel Comp E4340 FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Qn-p-416,type 2.class 2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unjf	Fastener Length:	0.980 Inches Minimum And 1.010 Inches Maximum
Width Between Flats:0.429 Inches Minimum And 0.439 Inches MaximumGrip Diameter:0.2485 Inches Minimum And 0.2495 Inches MaximumNominal Thread Diameter:0.250 InchesGrip Length:0.615 Inches Minimum And 0.635 Inches MaximumThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Fastener And 40.0 Rockwell C Maximum FastenerSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripMaterial:Plastic Polyamide Locking FeatureMaterial:Steel Comp E4340 Fastener Or Steel Comp 8740 FastenerMaterial:Comp E4340 Fastener Or Steel Comp 8740 FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment:Qu-p-416.type 2,class 2 Fed Spec Single Treatment Response FastenerMarea Series Designator:Unif	Head Style:	Dished Hexagon
Grip Diameter:0.2485 Inches Minimu And 0.2495 Inches MaximumNominal Thread Diameter:0.250 InchesGrip Length:0.615 Inches Minimu And 0.635 Inches MaximumThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Fastener And 40.0 Rockwell C Maximum FastenerSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Descion Comp E4340 Fastener Or Mil-S-6049 Mil Spec 2nd Material Response Fastener Or Mil-S-6049 Mil Spec 2nd Spec Single Tre	Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Nominal Thread Diameter:0.250 InchesGrip Length:0.615 Inches Minimum And 0.635 Inches MaximumThread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Fastener And 40.0 Rockwell C Maximum FastenerSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Plastic Polyamide Locking FeatureMaterial:Stel Comp E4340 Fastener Or Stel Comp 8740 FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment:Orp-416.type 2,class 2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unif	Width Between Flats:	0.429 Inches Minimum And 0.439 Inches Maximum
Grip Length:0.615 Inches Minimum And 0.635 Inches MaximumGrip Length:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Fastener And 40.0 Rockwell C Maximum FastenerSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Plastic Polyamide Locking FeatureMaterial:Kel Comp E4340 Fastener Or Steel Comp 8740 FastenerMaterial Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Fastener Or Mil-s-6049 Mil Spec 2nd Material Response Fastener Or Ams6322 Assn StdSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment:Oq-p-416,type 2,class 2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unjf	Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Thread Quantity Per Inch:28Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Fastener And 40.0 Rockwell C Maximum FastenerSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Pastic Polyamide Locking FeatureMaterial:Stel Comp E4340 Fastener Or Stel Comp 8740 FastenerMaterial Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Fastener Or Mil-s-6049 Mil Spec 2nd Material Response Fastener Or Ams6322 Assn StdSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:q-p-416,type 2,class 2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unif	Nominal Thread Diameter:	0.250 Inches
Minimum Tensile Strength:160000 Pounds Per Square InchHardness Rating:36.0 Rockwell C Minimum Fastener And 40.0 Rockwell C Maximum FastenerSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Plastic Polyamide Locking FeatureMaterial:Steel Comp E4340 Fastener Or Steel Comp 8740 FastenerMaterial Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Fastener Or Mil-s-6049 Mil Spec 2nd Material Response Fastener Or Ams6322 Assn Std 2nd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Q-p-416,type 2,class 2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unjf	Grip Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Hardness Rating:36.0 Rockwell C Minimum Fastener And 40.0 Rockwell C Maximum FastenerSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Plastic Polyamide Locking FeatureMaterial:Steel Comp E4340 Fastener Or Steel Comp 8740 FastenerMaterial Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Fastener Or Mil-s-6049 Mil Spec 2nd Material Response Fastener Or Ams6322 Assn StdSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Q-p-416,type 2,class 2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unjf	Thread Quantity Per Inch:	28
Surface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Plastic Polyamide Locking FeatureMaterial:Steel Comp E4340 Fastener Or Steel Comp 8740 FastenerMaterial Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Fastener Or Mil-s-6049 Mil Spec 2nd Material Response Fastener Or Ams6322 Assn Std 2nd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment:Oq-p-416,type 2,class 2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unjf	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Surface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:9 Hastic Polyamide Locking FeatureMaterial:Steel Comp E4340 Fastener Or Steel Comp 8740 FastenerMaterial Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Fastener Or Mil-s-6049 Mil Spec 2nd Material Response Fastener Or Ams6322 Assn Std 2nd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unjf	Hardness Rating:	36.0 Rockwell C Minimum Fastener And 40.0 Rockwell C Maximum Fastener
Surface Finish:32.0 Microinches ThreadsMaterial:Plastic Polyamide Locking FeatureMaterial:Steel Comp E4340 Fastener Or Steel Comp 8740 FastenerMaterial Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Fastener Or Mil-s-6049 Mil Spec 2nd Material Response Fastener Or Ams6322 Assn Std 2nd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Qu-p-416,type 2,class 2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unjf	Surface Finish:	32.0 Microinches Bearing Surface Of Head
Material:Plastic Polyamide Locking FeatureMaterial:Steel Comp E4340 Fastener Or Steel Comp 8740 FastenerMaterial Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Fastener Or Mil-s-6049 Mil Spec 2nd Material Response Fastener Or Ams6322 Assn Std 2nd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Qa-p-416,type 2,class 2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unjf	Surface Finish:	32.0 Microinches Grip
Material:Steel Comp E4340 Fastener Or Steel Comp 8740 FastenerMaterial Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Fastener Or Mil-s-6049 Mil Spec 2nd Material Response Fastener Or Ams6322 Assn Std 2nd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unjf	Surface Finish:	32.0 Microinches Threads
Material Document And Classification:Mil-s-5000 Mil Spec 1st Material Response Fastener Or Mil-s-6049 Mil Spec 2nd Material Response Fastener Or Ams6322 Assn Std 2nd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unjf	Material:	Plastic Polyamide Locking Feature
Material Document And Classification:2nd Material Response FastenerSurface Treatment:Cadmium Fastener And Chromate FastenerSurface Treatment Document And Classification:Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unjf	Material:	Steel Comp E4340 Fastener Or Steel Comp 8740 Fastener
Surface Treatment Document And Classification:Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response FastenerThread Series Designator:Unjf	Material Document And Classification:	
Classification: Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Fastener Thread Series Designator: Unjf	Surface Treatment:	Cadmium Fastener And Chromate Fastener
		Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Fastener
Specification/standard Data: 80205-nas6204 Professional/industrial Association Standard	Thread Series Designator:	Unjf
	Specification/standard Data:	80205-nas6204 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/shear+bolts/NAS6204L10</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.