

P/N NAS6204L10

Description

Fastener Length: 0-63/64", Thread: 1/4-28, Thread Length: 25/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS6204L10

Minimum Qty (MOQ): 15 EA

NSN: 5306-01-285-2747

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS6204L10 Specifications

Thread Direction: Right-hand O.345 Inches Minimum And 0.395 Inches Maximum Fastener Length: 0.980 Inches Minimum And 1.010 Inches Maximum Head Style: Dished Hexagon Head Height: 0.125 Inches Minimum And 0.140 Inches Maximum Width Between Flats: 0.429 Inches Minimum And 0.439 Inches Maximum Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum Nominal Thread Diameter: 0.250 Inches Grip Length: 0.615 Inches Minimum And 0.635 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Fastener And 40.0 Rockwell C Maximum Fastener Surface Finish: 32.0 Microinches Bearing Surface Of Head	Thread Class:	3a
Thread Length: 0.345 Inches Minimum And 0.395 Inches Maximum 0.980 Inches Minimum And 1.010 Inches Maximum Dished Hexagon Head Height: 0.125 Inches Minimum And 0.140 Inches Maximum Width Between Flats: 0.429 Inches Minimum And 0.439 Inches Maximum Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum Nominal Thread Diameter: 0.250 Inches Grip Length: 0.615 Inches Minimum And 0.635 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Fastener And 40.0 Rockwell C Maximum Fastener Surface Finish: 32.0 Microinches Bearing Surface Of Head		
Fastener Length: 0.980 Inches Minimum And 1.010 Inches Maximum Dished Hexagon Head Height: 0.125 Inches Minimum And 0.140 Inches Maximum Width Between Flats: 0.429 Inches Minimum And 0.439 Inches Maximum Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum Nominal Thread Diameter: 0.250 Inches Grip Length: 0.615 Inches Minimum And 0.635 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Fastener And 40.0 Rockwell C Maximum Fastener Surface Finish: 32.0 Microinches Bearing Surface Of Head		
Head Style: Dished Hexagon 0.125 Inches Minimum And 0.140 Inches Maximum 0.429 Inches Minimum And 0.439 Inches Maximum 0.2485 Inches Minimum And 0.2495 Inches Maximum 0.2485 Inches Minimum And 0.2495 Inches Maximum Nominal Thread Diameter: 0.250 Inches Grip Length: 0.615 Inches Minimum And 0.635 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Fastener And 40.0 Rockwell C Maximum Fastener Surface Finish: 32.0 Microinches Bearing Surface Of Head	Thread Length:	0.345 Inches Minimum And 0.395 Inches Maximum
Head Height: 0.125 Inches Minimum And 0.140 Inches Maximum 0.429 Inches Minimum And 0.439 Inches Maximum Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum Nominal Thread Diameter: 0.250 Inches Grip Length: 0.615 Inches Minimum And 0.635 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Fastener And 40.0 Rockwell C Maximum Fastener Surface Finish: 32.0 Microinches Bearing Surface Of Head	Fastener Length:	0.980 Inches Minimum And 1.010 Inches Maximum
Width Between Flats: 0.429 Inches Minimum And 0.439 Inches Maximum 0.2485 Inches Minimum And 0.2495 Inches Maximum Nominal Thread Diameter: 0.250 Inches Grip Length: 0.615 Inches Minimum And 0.635 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Fastener And 40.0 Rockwell C Maximum Fastener Surface Finish: 32.0 Microinches Bearing Surface Of Head	Head Style:	Dished Hexagon
Grip Diameter: 0.2485 Inches Minimum And 0.2495 Inches Maximum 0.250 Inches 0.615 Inches Minimum And 0.635 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Fastener And 40.0 Rockwell C Maximum Fastener Surface Finish: 32.0 Microinches Bearing Surface Of Head	Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Nominal Thread Diameter: 0.250 Inches Grip Length: 0.615 Inches Minimum And 0.635 Inches Maximum Thread Quantity Per Inch: 28 Minimum Tensile Strength: 160000 Pounds Per Square Inch Hardness Rating: 36.0 Rockwell C Minimum Fastener And 40.0 Rockwell C Maximum Fastener Surface Finish: 32.0 Microinches Bearing Surface Of Head	Width Between Flats:	0.429 Inches Minimum And 0.439 Inches Maximum
Grip Length: O.615 Inches Minimum And O.635 Inches Maximum Thread Quantity Per Inch: Minimum Tensile Strength: 160000 Pounds Per Square Inch 36.0 Rockwell C Minimum Fastener And 40.0 Rockwell C Maximum Fastener Surface Finish: 32.0 Microinches Bearing Surface Of Head	Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Thread Quantity Per Inch: Minimum Tensile Strength: 160000 Pounds Per Square Inch 36.0 Rockwell C Minimum Fastener And 40.0 Rockwell C Maximum Fastener Surface Finish: 32.0 Microinches Bearing Surface Of Head	Nominal Thread Diameter:	0.250 Inches
Minimum Tensile Strength: 160000 Pounds Per Square Inch 36.0 Rockwell C Minimum Fastener And 40.0 Rockwell C Maximum Fastener Surface Finish: 32.0 Microinches Bearing Surface Of Head	Grip Length:	0.615 Inches Minimum And 0.635 Inches Maximum
Hardness Rating: 36.0 Rockwell C Minimum Fastener And 40.0 Rockwell C Maximum Fastener Surface Finish: 32.0 Microinches Bearing Surface Of Head	Thread Quantity Per Inch:	28
Surface Finish: 32.0 Microinches Bearing Surface Of Head	Minimum Tensile Strength:	160000 Pounds Per Square Inch
	Hardness Rating:	36.0 Rockwell C Minimum Fastener And 40.0 Rockwell C Maximum Fastener
Surface Finish: 32.0 Microinches Grin	Surface Finish:	32.0 Microinches Bearing Surface Of Head
52.0 Pilefolleties Orip	Surface Finish:	32.0 Microinches Grip
Surface Finish: 32.0 Microinches Threads	Surface Finish:	32.0 Microinches Threads
Material: Plastic Polyamide Locking Feature	Material:	Plastic Polyamide Locking Feature
Material: Steel Comp E4340 Fastener Or Steel Comp 8740 Fastener	Material:	Steel Comp E4340 Fastener Or Steel Comp 8740 Fastener
Material Document And Classification: Mil-s-5000 Mil Spec 1st Material Response Fastener Or Mil-s-6049 Mil Spec 2nd Material Response Fastener Or Ams6322 Assn Std 2nd Material Response Fastener	Material Document And Classification:	
Surface Treatment: Cadmium Fastener And Chromate Fastener	Surface Treatment:	Cadmium Fastener And Chromate Fastener
Og-p-416 type 2 class 2 Fed Spec Single Treatment Response Fastener	Surface Treatment Document And Classification:	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Fastener
Thread Series Designator: Unjf	Thread Series Designator:	Unjf
Specification/standard Data: 80205-nas6204 Professional/industrial Association Standard	Specification/standard Data:	80205-nas6204 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6204L10 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.