

P/N NAS6204L17

Description

Fastener Length: 1-7/16", Thread: 1/4-28, Thread Length: 25/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS6204L17
Minimum Qty (MOQ): 5 EA

NSN: 5306-01-083-6452

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N NAS6204L17 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.345 Inches Minimum And 0.395 Inches Maximum
Fastener Length:	1.417 Inches Minimum And 1.447 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.429 Inches Minimum And 0.439 Inches Maximum
Locking Feature:	Patch Threads Or Pellet Threads Or Strip Threads
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	1.052 Inches Minimum And 1.072 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Plastic Polyamide Locking Feature
Material:	Steel Comp E4340 Fastener Or Steel Comp 8740 Fastener
Material Document And Classification:	Mil-s-6049 Mil Spec 2nd Material Response Fastener Or Ams 6322 Assn Std 2nd Material Response Fastener Or Mil-s-5000 Mil Spec 1st Material Response Fastener
Surface Treatment:	Cadmium Fastener And Chromate Fastener
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Mil Spec 1st Treatment Response Fastener
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6204 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6204L17 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6204L17 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6204L17 and selecting the quantity you want then click "add to cart".