

Description

Fastener Length: 1-", Thread: 1/4-28, Thread Length: "

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS6204L20 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-01-482-2246 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |

NO IMAGE
AVAILABLE

P/N NAS6204L20 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.370 Inches Nominal |
| Fastener Length: | 1.620 Inches Nominal |
| Head Style: | Dished Hexagon |
| Head Height: | 0.125 Inches Minimum And 0.140 Inches Maximum |
| Width Between Flats: | 0.429 Inches Minimum And 0.439 Inches Maximum |
| Grip Diameter: | 0.248 Inches Minimum And 0.249 Inches Maximum |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 1.250 Inches Nominal |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Material: | Plastic Locking Feature |
| Material: | Steel Comp 4340 Fastener Or Steel Comp 8740 Fastener |
| Material Document And Classification: | Ams6415 Assn Std 1st Material Response Fastener Or Ams6322 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 2nd Material Response Fastener |
| Surface Treatment: | Cadmium Bearing Surface Of Head |
| Surface Treatment Document And Classification: | Qq-p-416, Ty11, Cl2 Fed Spec Single Treatment Response Bearing Surface Of Head |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6204L20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.