

**Description**

Fastener Length: 1-", Thread: 1/4-28, Thread Length: "

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS6204L20
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-482-2246
Schedule B:	7318.15.8085
ECCN:	9A991



\* See page 2 for technical characteristics

## P/N NAS6204L20 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.370 Inches Nominal
<b>Fastener Length:</b>	1.620 Inches Nominal
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.125 Inches Minimum And 0.140 Inches Maximum
<b>Width Between Flats:</b>	0.429 Inches Minimum And 0.439 Inches Maximum
<b>Grip Diameter:</b>	0.248 Inches Minimum And 0.249 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Grip Length:</b>	1.250 Inches Nominal
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Material:</b>	Plastic Locking Feature
<b>Material:</b>	Steel Comp 4340 Fastener Or Steel Comp 8740 Fastener
<b>Material Document And Classification:</b>	Ams6415 Assn Std 1st Material Response Fastener Or Ams6322 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 2nd Material Response Fastener
<b>Surface Treatment:</b>	Cadmium Bearing Surface Of Head
<b>Surface Treatment Document And Classification:</b>	Qq-p-416, Ty11, Cl2 Fed Spec Single Treatment Response Bearing Surface Of Head
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6204L20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.