

Description

Fastener Length: 1-", Thread: 1/4-28, Thread Length: "

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6204L20
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-482-2246
Schedule B:	7318.15.8085
ECCN:	9A991

NO IMAGE
AVAILABLE

P/N NAS6204L20 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.370 Inches Nominal
Fastener Length:	1.620 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.429 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	0.248 Inches Minimum And 0.249 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	1.250 Inches Nominal
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Plastic Locking Feature
Material:	Steel Comp 4340 Fastener Or Steel Comp 8740 Fastener
Material Document And Classification:	Ams6415 Assn Std 1st Material Response Fastener Or Ams6322 Assn Std 2nd Material Response Fastener Or Mil-s-6049 Mil Spec 2nd Material Response Fastener
Surface Treatment:	Cadmium Bearing Surface Of Head
Surface Treatment Document And Classification:	Qq-p-416, Ty11, Cl2 Fed Spec Single Treatment Response Bearing Surface Of Head
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6204L20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.