

Description

Fastener Length: 3/4", Hole Diameter: 3/64", Thread: 1/4-28, Thread Length: "

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6204L7H
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-521-2933
Schedule B:	7318.15.8085
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N NAS6204L7H Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.370 Inches Nominal
Fastener Length:	0.808 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.429 Inches Minimum And 0.439 Inches Maximum
Hole Diameter:	0.048 Inches Minimum And 0.058 Inches Maximum
Locking Feature:	Patch Threads Or Pellet Threads Or Strip Threads
Grip Diameter:	0.248 Inches Minimum And 0.249 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.438 Inches Nominal
Hole Quantity:	3
Hole Type:	Drilled
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hole Configuration Style:	Hexagon Corners
Material:	Plastic Polyamide Locking Feature
Material:	Steel Comp 4340 Bearing Surface Of Head Or Steel Comp 8740 Bearing Surface Of Head
Material Document And Classification:	Ams 6415 Assn Std 1st Material Response Bearing Surface Of Head Or Ams 6322 Assn Std 2nd Material Response Bearing Surface Of Head Or Mil-s-6049 Mil Spec 2nd Material Response Bearing Surface Of Head
Material Document And Classification:	Mil-dtl-18240 Mil Spec Single Material Response Locking Feature
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Tyii, Cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6204 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6204L7H> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.