

**Description**

Fastener Length: 7/8", Thread: 1/4-28, Thread Length: 25/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS6204P8                                 |
| Minimum Qty (MOQ):      | 10 EA                                     |
| NSN:                    | 5306-01-337-4854                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS6204P8 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.345 Inches Minimum And 0.395 Inches Maximum   |
| <b>Fastener Length:</b>                               | 0.855 Inches Minimum And 0.885 Inches Maximum   |
| <b>Head Style:</b>                                    | Dished Hexagon  |
| <b>Head Height:</b>                                   | 0.125 Inches Minimum And 0.140 Inches Maximum   |
| <b>Width Between Flats:</b>                           | 0.429 Inches Minimum And 0.439 Inches Maximum   |
| <b>Locking Feature:</b>                               | Patch Threads   |
| <b>Grip Diameter:</b>                                 | 0.2485 Inches Minimum And 0.2495 Inches Maximum   |
| <b>Nominal Thread Diameter:</b>                       | 0.250 Inches  |
| <b>Grip Length:</b>                                   | 0.490 Inches Minimum And 0.510 Inches Maximum   |
| <b>Thread Quantity Per Inch:</b>                      | 28  |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch   |
| <b>Hardness Rating:</b>                               | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall   |
| <b>Material:</b>                                      | Plastic Polyamide Locking Featuresteel Comp E4340 Fastener Or Steel Comp 8740 Fastener  |
| <b>Material Document And Classification:</b>          | Mil-s-5000 Mil Spec 1st Material Response Fastener Or Mil-s-6049 Mil Spec 2nd Material Response Fastener Or Ams6322 Assn Std 2nd Material Response Fastener |
| <b>Surface Treatment:</b>                             | Cadmium Fastener And Chromate Fastener  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Fastener   |
| <b>Thread Series Designator:</b>                      | Unjf  |
| <b>Specification/standard Data:</b>                   | 80205-nas6206 Professional/Industrial Association Standard  |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6204P8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.