

**Description**

Fastener Length: 1-9/64", Thread: 5/16-24, Thread Length: 7/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS620511X                                |
| Minimum Qty (MOQ):      | 1 EA                                      |
| NSN:                    | 5306-01-409-1096                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS6205-11X Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.438 Inches Nominal  |
| <b>Fastener Length:</b>                               | 1.111 Inches Minimum And 1.141 Inches Maximum                       |
| <b>Head Style:</b>                                    | Dished Hexagon  |
| <b>Head Height:</b>                                   | 0.156 Inches Minimum And 0.171 Inches Maximum                       |
| <b>Width Between Flats:</b>                           | 0.492 Inches Minimum And 0.502 Inches Maximum                       |
| <b>Grip Diameter:</b>                                 | 0.3276 Inches Nominal   |
| <b>Nominal Thread Diameter:</b>                       | 0.3125 Inches   |
| <b>Grip Length:</b>                                   | 0.678 Inches Minimum And 0.698 Inches Maximum                       |
| <b>Thread Quantity Per Inch:</b>                      | 24  |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch                                       |
| <b>Hardness Rating:</b>                               | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| <b>Material:</b>                                      | Steel Comp E4340 Overall Or Steel Comp 8740 Overall                 |
| <b>Surface Treatment:</b>                             | Cadmium Overall And Chromate Overall                                |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-416, Ty 2, Cl 2 Fed Spec All Treatment Responses Overall       |
| <b>Thread Series Designator:</b>                      | Unjf  |
| <b>Specification/standard Data:</b>                   | 80205-nas6205 Professional/industrial Association Standard          |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6205-11X> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.