

P/N NAS6205-11X

Military-Fasteners.com

Description

Fastener Length: 1-9/64", Thread: 5/16-24, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

| SKU / Model: | NAS620511X |
|-------------------------|---|
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-01-409-1096 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N NAS6205-11X Specifications

| Thread Class: | 3a |
|--|---|
| Thread Direction: | Right-hand |
| Thread Length: | 0.438 Inches Nominal |
| Fastener Length: | 1.111 Inches Minimum And 1.141 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.156 Inches Minimum And 0.171 Inches Maximum |
| Width Between Flats: | 0.492 Inches Minimum And 0.502 Inches Maximum |
| Grip Diameter: | 0.3276 Inches Nominal |
| Nominal Thread Diameter: | 0.3125 Inches |
| Grip Length: | 0.678 Inches Minimum And 0.698 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall |
| Material: | Steel Comp E4340 Overall Or Steel Comp 8740 Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416, Ty 2, Cl 2 Fed Spec All Treatment Responses Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas6205 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/shear+bolts/NAS6205-11X</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.