

# P/N NAS6205-17

Military-Fasteners.com

#### Description

length: 1.50", grip: 1.062", thread: 5/16-24, hex head, tension, short thread, cadmium plated alloy steel, NAS6205 series bolt

\* Manufacturer certifications are shipped with your order  $\underline{\mathsf{FREE}}$  of charge

### Order this part online

#### **Additional Information**

| SKU / Model:            | NAS620517                                 |
|-------------------------|---|
| Minimum Qty (MOQ):      | 10  |
| NSN:                    | 5306-01-193-4503                          |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N NAS6205-17 Specifications

| Thread Class:                                     | За   |
|---|--|
| Thread Direction:                                 | Right-hand   |
| Thread Length:                                    | 0.413 Inches Minimum And 0.463 Inches Maximum  |
| Fastener Length:                                  | 1.485 Inches Minimum And 1.515 Inches Maximum  |
| Head Style:                                       | Dished Hexagon   |
| Head Height:                                      | 0.156 Inches Minimum And 0.171 Inches Maximum  |
| Width Between Flats:                              | 0.492 Inches Minimum And 0.502 Inches Maximum  |
| Grip Diameter:                                    | 0.3110 Inches Minimum And 0.3120 Inches Maximum  |
| Nominal Thread Diameter:                          | 0.312 Inches   |
| Grip Length:                                      | 1.052 Inches Minimum And 1.072 Inches Maximum  |
| Thread Quantity Per Inch:                         | 24   |
| Minimum Tensile Strength:                         | 160000 Pounds Per Square Inch  |
| Hardness Rating:                                  | 36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall  |
| Surface Finish:                                   | 32.0 Microinches Bearing Surface Of Head   |
| Surface Finish:                                   | 32.0 Microinches Grip  |
| Surface Finish:                                   | 32.0 Microinches Threads   |
| Material:   | Steel Comp E4340 Overall Or Steel Comp 8740 Overall  |
| Material Document And Classification:             | Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std<br>2nd Material Response Overall |
| Surface Treatment:                                | Cadmium Overall And Chromate Overall   |
| Surface Treatment Document And<br>Classification: | Qq-p-416,ty 2 Cl 2 Fed Spec Single Treatment Response Overall  |
| Thread Series Designator:                         | Unjf   |
| Specification/standard Data:                      | 80205-nas6205 Professional/industrial Association Standard   |

### How to Order

Order this shear bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/shear+bolts/NAS6205-17</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.