

## **P/N NAS6205-17X**

## **Description**

Fastener Length: 1-33/64", Thread: 5/16-28, Thread Length: 7/16"

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model: NAS620517X

Minimum Qty (MOQ): 45 EA

NSN: 5306-01-436-7672

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS6205-17X Specifications**

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.438 Inches Nominal
Fastener Length:	1.486 Inches Minimum And 1.516 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.156 Inches Minimum And 0.171 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Shoulder Diameter:	0.3266 Inches Minimum First Shoulder And 0.3276 Inches Maximum First Shoulder
Shoulder Length:	0.740 Inches Minimum First Shoulder And 0.760 Inches Maximum First Shoulder
Nominal Thread Diameter:	0.3125 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Minimum Yield Strength:	95000 Pounds Per Square Inch
Shoulder Shape:	Round First Shoulder
Material:	Steel Comp 4340 Overall Or Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-5000 Mil Spec 2nd Material Response Overall Or Mil-s-6049 Mil Spec 3rd Material Response Overall Or Ams 6322 Assn Std 3rd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416, Type 2, Class 2 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6205 Professional/industrial Association Standard

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/shear+bolts/NAS6205-17X">https://military-fasteners.com/bolts/shear+bolts/NAS6205-17X</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/shear+bolts/NAS6205-17X">https://military-fasteners.com/bolts/shear+bolts/NAS6205-17X</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/shear+bolts/NAS6205-17X">https://military-fasteners.com/bolts/shear+bolts/NAS6205-17X</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/shear+bolts/NAS6205-17X">https://military-fasteners.com/bolts/shear+bolts/NAS6205-17X</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/shear+bolts/nas6205-17X">https://military-fasteners.com/bolts/shear+bolts/nas6205-17X</a> and selecting the quantity you want then click "add to cart".