

**Description**

length: 1.626", grip: 1.188", thread: 5/16-24, hex head, drilled shank, tension, short thread, cadmium plated alloy steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS620519D
Minimum Qty (MOQ):	5
NSN:	5306-01-142-2121
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N NAS6205-19D Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.438 Inches Nominal
<b>Fastener Length:</b>	1.626 Inches Nominal
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.163 Inches Nominal
<b>Width Between Flats:</b>	0.500 Inches Nominal
<b>Grip Diameter:</b>	0.3130 Inches Nominal
<b>Shank Unthreaded Hole Diameter:</b>	0.112 Inches Nominal First Hole
<b>Nominal Thread Diameter:</b>	0.313 Inches
<b>Grip Length:</b>	1.188 Inches Nominal
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	1.444 Inches Nominal First Hole
<b>Material:</b>	Steel Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas6205 Professional/Industrial Association Standard

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6205-19D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.