



★ FASTENERS

Military-Fasteners.com

**P/N NAS6205-22**

## Description

length: 1.813", grip: 1.375", thread: 5/16-24, hex head, short thread, cadmium plated alloy steel, NAS6205 series bolt

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS620522
Minimum Qty (MOQ):	25
NSN:	5306-01-131-2931
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N NAS6205-22 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.413 Inches Minimum And 0.463 Inches Maximum
<b>Fastener Length:</b>	1.798 Inches Minimum And 1.828 Inches Maximum
<b>Head Style:</b>	Undercut Hexagon
<b>Head Height:</b>	0.156 Inches Minimum And 0.171 Inches Maximum
<b>Width Between Flats:</b>	0.492 Inches Minimum And 0.502 Inches Maximum
<b>Grip Diameter:</b>	0.3110 Inches Minimum And 0.3120 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.312 Inches
<b>Grip Length:</b>	1.365 Inches Minimum And 1.385 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Surface Finish:</b>	32.0 Microinches Bearing Surface Of Head
<b>Surface Finish:</b>	32.0 Microinches Threads
<b>Material:</b>	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty2 Cl2 Fed Spec All Treatment Responses Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas6205 Professional/Industrial Association Standard

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6205-22> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.