

Description

Fastener Length: 1-53/64", Thread: 1/4-24, Thread Length: 29/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS620522X |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-01-275-6793 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS6205-22X Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.413 Inches Minimum And 0.463 Inches Maximum |
| Fastener Length: | 1.798 Inches Minimum And 1.828 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.156 Inches Minimum And 0.171 Inches Maximum |
| Width Between Flats: | 0.492 Inches Minimum And 0.502 Inches Maximum |
| Shoulder Diameter: | 0.3266 Inches Minimum First Shoulder And 0.3276 Inches Maximum First Shoulder |
| Shoulder Length: | 1.365 Inches Minimum First Shoulder And 1.385 Inches Maximum First Shoulder |
| Nominal Thread Diameter: | 0.312 Inches |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Shoulder Shape: | Round First Shoulder |
| Material: | Steel Comp E4340 Overall Or Steel Comp 8740 Overall |
| Material Document And Classification: | Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas6205 Professional/industrial Association Standard |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6205-22X> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.