

## P/N NAS6205-24D

### **Description**

length: 1.938", grip: 1.500", thread: 5/16-24, hex head drilled shank tension short thread cadmium plated alloy steel

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS620524D

Minimum Qty (MOQ): 10

NSN: 5306-01-176-8328

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)





<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS6205-24D Specifications

3a
Right-hand
0.438 Inches Nominal
1.923 Inches Minimum And 1.953 Inches Maximum
Dished Hexagon
0.156 Inches Minimum And 0.171 Inches Maximum
0.492 Inches Minimum And 0.502 Inches Maximum
0.3110 Inches Minimum And 0.3120 Inches Maximum
0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
0.312 Inches
1.490 Inches Minimum And 1.510 Inches Maximum
24
160000 Pounds Per Square Inch
36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
1.746 Inches Minimum First Hole And 1.766 Inches Maximum First Hole
Steel Overall
Mil-s-5000,4340 Or E4340 Mil Spec Single Material Response Overall
Cadmium Overall
Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Unjf
80205-nas6205 Professional/industrial Association Standard

## **How to Order**

Order this shear bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/shear+bolts/NAS6205-24D">https://military-fasteners.com/bolts/shear+bolts/NAS6205-24D</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.