

Description

length: 2.313", grip: 1.875", thread: 5/16-24, hex head - drilled shank - tension - short thread - cadmium plated alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS620530D
Minimum Qty (MOQ):	2
NSN:	5306-01-438-2149
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS6205-30D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.463 Inches Maximum
Fastener Length:	2.313 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.156 Inches Minimum And 0.171 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Hole Diameter:	0.070 Inches Minimum And 0.080 Inches Maximum
Grip Diameter:	0.311 Inches Nominal
Shank Unthreaded Hole Diameter:	0.081 Inches Nominal First Hole
Nominal Thread Diameter:	0.313 Inches
Grip Length:	1.885 Inches Maximum
Hole Quantity:	3
Hole Type:	Drilled
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hole Configuration Style:	Hexagon Corners
Distance From Head Largest Bearing Surface To Shank Hole Center:	2.131 Inches Nominal First Hole
Surface Finish:	32.0 Microinches Head
Material:	Plastic Locking Feature
Material:	Steel Head
Surface Treatment:	Cadmium Head
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6205 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6205-30D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.