

Description

length: 2.501", grip: 2.063", thread: 5/16-24, hex head - drilled shank - tension - short thread - cadmium plated alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS620533D
Minimum Qty (MOQ):	1
NSN:	5306-01-265-4904
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS6205-33D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.413 Inches Minimum And 0.463 Inches Maximum
Fastener Length:	2.486 Inches Minimum And 2.516 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.156 Inches Minimum And 0.171 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Grip Diameter:	0.3110 Inches Minimum And 0.3120 Inches Maximum
Shank Unthreaded Hole Diameter:	0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
Nominal Thread Diameter:	0.312 Inches
Grip Length:	2.053 Inches Minimum And 2.073 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Distance From Head Largest Bearing Surface To Shank Hole Center:	2.294 Inches Minimum First Hole And 2.344 Inches Maximum First Hole
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6205 Professional/Industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6205-33D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.