

Description

Fastener Length: 2-53/64", Thread: 5/16-24, Thread Length: 7/16

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS620538D
Minimum Qty (MOQ):	5
NSN:	5306-01-494-0256
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS6205-38D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.438 Inches Nominal
Fastener Length:	2.798 Inches Minimum And 2.828 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.158 Inches Minimum And 0.171 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Grip Diameter:	0.3110 Inches Minimum And 0.3120 Inches Maximum
End Item Identification:	1520-01-125-5476
Nominal Thread Diameter:	0.3125 Inches
Grip Length:	2.365 Inches Minimum And 2.385 Inches Maximum
Thread Quantity Per Inch:	24
Distance From Head Largest Bearing Surface To Shank Hole Center:	2.621 Inches Minimum First Hole And 2.641 Inches Maximum First Hole
Material:	Steel Overall
Material Document And Classification:	Nas 4002 National Spec Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Type II, Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6205 Professional/Industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6205-38D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.