

## Description

Fastener Length: 3-43/64", Thread: 5/16-24, Thread Length: 7/16",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS620549D
Minimum Qty (MOQ):	1
NSN:	5306-01-614-1499
Schedule B:	7318.15.8085
ECCN:	EAR99



## P/N NAS6205-49D Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.438 Inches Nominal
<b>Fastener Length:</b>	3.647 Inches Minimum And 3.682 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.156 Inches Minimum And 0.171 Inches Maximum
<b>Width Between Flats:</b>	0.492 Inches Minimum And 0.502 Inches Maximum
<b>Grip Diameter:</b>	0.3110 Inches Minimum And 0.3120 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.313 Inches
<b>Grip Length:</b>	3.053 Inches Minimum And 3.073 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Material:</b>	Steel Comp E4340 Or Steel Comp 4340 Or Steel Comp 8740 Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416, Type 2, Class 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6205-49D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.