

Description

Fastener Length: 3-61/64", Thread: 5/16-24, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS620551D |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-01-614-1497 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |



* See page 2 for technical characteristics

P/N NAS6205-51D Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.438 Inches Nominal |
| Fastener Length: | 3.922 Inches Minimum And 3.957 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.156 Inches Minimum And 0.171 Inches Maximum |
| Width Between Flats: | 0.492 Inches Minimum And 0.502 Inches Maximum |
| Grip Diameter: | 0.3110 Inches Minimum And 0.3120 Inches Maximum |
| Nominal Thread Diameter: | 0.313 Inches |
| Grip Length: | 3.278 Inches Minimum And 3.298 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Material: | Steel Comp E4340 Or Steel Comp 4340 Or Steel Comp 8740 Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416, Type 2, Class 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6205-51D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.