

**Description**

Fastener Length: 3-53/64", Thread: 1/4-24, Thread Length: 7/16",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS620554
Minimum Qty (MOQ):	2
NSN:	5306-01-493-4127
Schedule B:	7318.15.8085
ECCN:	EAR99



## P/N NAS6205-54 Specifications

<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.438 Inches Nominal
<b>Fastener Length:</b>	3.798 Inches Minimum And 3.828 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.156 Inches Minimum And 0.171 Inches Maximum
<b>Width Between Flats:</b>	0.3070 Inches Minimum And 0.3075 Inches Maximum
<b>Grip Diameter:</b>	0.3070 Inches Minimum And 0.3075 Inches Maximum
<b>Point Diameter:</b>	0.302 Inches Minimum And 0.306 Inches Maximum
<b>Point Style:</b>	Flat
<b>Nominal Thread Diameter:</b>	0.312 Inches
<b>Grip Length:</b>	3.365 Inches Minimum And 3.385 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Part Name Assigned By Controlling Agency:</b>	Bolt, Tension, Hex Head, Close Tolerance, Alloy Steel, Short Thread
<b>Material:</b>	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	Ams6439 Assn Std 1st Material Response Overall Or Ams6484 Assn Std 2nd Material Response Overall Or Ams6322 Assn Std 3rd Material Response Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	11-p-416, Ty2cl2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6205-54> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.