

Description

Fastener Length: 3-53/64", Thread: 1/4-24, Thread Length: 7/16",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS620554
Minimum Qty (MOQ):	2
NSN:	5306-01-493-4127
Schedule B:	7318.15.8085
ECCN:	EAR99



P/N NAS6205-54 Specifications

Thread Direction:	Right-hand
Thread Length:	0.438 Inches Nominal
Fastener Length:	3.798 Inches Minimum And 3.828 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.156 Inches Minimum And 0.171 Inches Maximum
Width Between Flats:	0.3070 Inches Minimum And 0.3075 Inches Maximum
Grip Diameter:	0.3070 Inches Minimum And 0.3075 Inches Maximum
Point Diameter:	0.302 Inches Minimum And 0.306 Inches Maximum
Point Style:	Flat
Nominal Thread Diameter:	0.312 Inches
Grip Length:	3.365 Inches Minimum And 3.385 Inches Maximum
Thread Quantity Per Inch:	24
Part Name Assigned By Controlling Agency:	Bolt, Tension, Hex Head, Close Tolerance, Alloy Steel, Short Thread
Material:	Steel Comp 4140 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Ams6439 Assn Std 1st Material Response Overall Or Ams6484 Assn Std 2nd Material Response Overall Or Ams6322 Assn Std 3rd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	11-p-416, Ty2cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6205-54> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.