

## **P/N NAS6205-7D**

### **Description**

length: 0.876", grip: 0.438", thread: 5/16-24, hex head, drilled shank, tension, short thread, cadmium plated alloy steel

\* Manufacturer certifications are shipped with your order EREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: NAS62057D

Minimum Qty (MOQ): 5

NSN: 5306-01-604-3184

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS6205-7D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.438 Inches Nominal
Fastener Length:	1.299 Inches Minimum And 1.329 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.156 Inches Minimum And 0.171 Inches Maximum
Width Between Flats:	0.492 Inches Minimum And 0.502 Inches Maximum
Grip Diameter:	0.311 Inches Minimum And 0.312 Inches Maximum
Shank Unthreaded Hole Diameter:	0.076 Inches Minimum And 0.086 Inches Maximum All Holes
End Item Identification:	C-130 Aircraft
Nominal Thread Diameter:	0.3125 Inches
Grip Length:	0.861 Inches Minimum And 0.891 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.132 Inches Nominal All Holes
Part Name Assigned By Controlling Agency:	Bolt, Tension, Hex Head, Close Tolerance
Special Features:	Embrittlement Requirement Per Nas4002
Material:	Steel Comp 4140 Or Steel Comp 4340 Or Steel Comp 8740 Overall
Material Document And Classification:	Ams6349 Assn Std Single Material Response Or Ams6382 Assn Std Single Material Response Or Ams6415 Assn Std Single Material Response Or Ams6484 Assn Std Single Material Response Or Ams6322 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Type 2, Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

# **How to Order**

Order this shear bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/shear+bolts/NAS6205-7D">https://military-fasteners.com/bolts/shear+bolts/NAS6205-7D</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/shear+bolts/NAS6205-7D">https://military-fasteners.com/bolts/shear+bolts/NAS6205-7D</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/shear+bolts/NAS6205-7D">https://military-fasteners.com/bolts/shear+bolts/NAS6205-7D</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/shear+bolts/NAS6205-7D">https://military-fasteners.com/bolts/shear+bolts/NAS6205-7D</a> and selecting the quantity you want then