

# **P/N NAS6205-84D**

### **Description**

Fastener Length: 5-45/64", Thread: 1/4-24, Thread Length: 7/16

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model:	NAS620584D
Minimum Qty (MOQ):	5
NSN:	5306-01-321-8727
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS6205-84D Specifications

3a
Right-hand
0.438 Inches Nominal
5.673 Inches Minimum And 5.703 Inches Maximum
Dished Hexagon
0.156 Inches Minimum And 0.171 Inches Maximum
0.492 Inches Minimum And 0.502 Inches Maximum
0.3110 Inches Minimum And 0.3120 Inches Maximum
0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
0.312 Inches
5.240 Inches Minimum And 5.260 Inches Maximum
24
160000 Pounds Per Square Inch
36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
7.673 Inches Minimum First Hole And 7.713 Inches Maximum First Hole
32.0 Microinches Bearing Surface Of Head
32.0 Microinches Grip
32.0 Microinches Threads
Steel Overall
Cadmium Overall And Chromate Overall
Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
Unjf
Oliji
F C C C C C C C C C C C C C C C C C C C

### **How to Order**

Order this shear bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/shear+bolts/NAS6205-84D">https://military-fasteners.com/bolts/shear+bolts/NAS6205-84D</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.