

Description

length: 2.016", grip: 1.562", thread: 3/8-24, hex head, drilled shank, tension, short thread, cadmium plated alloy steel, NAS6206 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS620625D |
| Minimum Qty (MOQ): | 2 |
| NSN: | 5306-01-210-4964 |
| Schedule B: | 7318.15.2095 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS6206-25D Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.429 Inches Minimum And 0.479 Inches Maximum |
| Fastener Length: | 2.001 Inches Minimum And 2.031 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.188 Inches Minimum And 0.203 Inches Maximum |
| Width Between Flats: | 0.554 Inches Minimum And 0.564 Inches Maximum |
| Grip Diameter: | 0.3735 Inches Minimum And 0.3745 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.106 Inches Minimum And 0.116 Inches Maximum First Hole |
| Nominal Thread Diameter: | 0.375 Inches |
| Grip Length: | 1.552 Inches Minimum And 1.572 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Hardness Rating: | 36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum Overall |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 1.808 Inches Minimum And 1.858 Inches Maximum First Hole |
| Surface Finish: | 32.0 Microinches Bearing Surface Of Head |
| Surface Finish: | 32.0 Microinches Grip |
| Surface Finish: | 32.0 Microinches Threads |
| Material: | Steel Comp E4340 Or Steel Comp 8740 Overall |
| Material Document And Classification: | Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6049 Mil Spec 2nd Material Response Or Ams6322 Assn Std 2nd Material Response Overall |
| Surface Treatment: | Cadmium And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,type 2 Class 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |
| Specification/standard Data: | 80205-nas6206 Professional/industrial Association Standard |

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6206-25D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.