

Description

length: 2.454", grip: 2.00", thread: 3/8-24, hex head, drilled shank, tension, short thread, cadmium plated alloy steel

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS620632D
Minimum Qty (MOQ):	10
NSN:	5306-01-142-2129
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS6206-32D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.454 Inches Nominal
Fastener Length:	2.454 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.195 Inches Nominal
Width Between Flats:	0.559 Inches Nominal
Grip Diameter:	0.3740 Inches Nominal
Shank Unthreaded Hole Diameter:	0.132 Inches Nominal First Hole
Nominal Thread Diameter:	0.375 Inches
Grip Length:	2.000 Inches Nominal
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	2.271 Inches Nominal First Hole
Material:	Steel Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6206 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6206-32D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.