

Description

length: 2.704", grip: 2.250", thread: 3/8-24, hex head, drilled shank, tension, short thread, cadmium plated alloy steel, NAS6206 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS620636D
Minimum Qty (MOQ):	5
NSN:	5306-01-212-4534
Schedule B:	7318.15.2095
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS6206-36D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.429 Inches Minimum And 0.479 Inches Maximum
Fastener Length:	2.689 Inches Minimum And 2.719 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.188 Inches Minimum And 0.203 Inches Maximum
Width Between Flats:	0.554 Inches Minimum And 0.584 Inches Maximum
Grip Diameter:	0.3735 Inches Minimum And 0.3745 Inches Maximum
Shank Unthreaded Hole Diameter:	0.106 Inches Minimum And 0.116 Inches Maximum First Hole
Nominal Thread Diameter:	0.375 Inches
Grip Length:	2.240 Inches Minimum And 2.260 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum And 40.0 Rockwell C Maximum Overall
Distance From Head Largest Bearing Surface To Shank Hole Center:	2.496 Inches Minimum And 2.546 Inches Maximum First Hole
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp E4340 Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Or Mil-s-6049 Mil Spec 2nd Material Response Or Ams 6322 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6206 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6206-36D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.