

Description

NAS6206-39 Shear Bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS620639
Minimum Qty (MOQ):	10
NSN:	5306-01-577-1667
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS6206-39 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.454 Inches Nominal
Fastener Length:	2.892 Nominal Inches
Head Style:	Dished Hexagon
Head Height:	0.188 Nominal Mils And 0.203 Nominal Centimeters
Width Between Flats:	0.554 Inches Minimum And 0.564 Inches Maximum
Grip Diameter:	0.373 Inches Minimum And 0.374 Inches Maximum
Shank Unthreaded Hole Diameter:	0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole
Nominal Thread Diameter:	0.375 Inches
Grip Length:	2.428 Inches Minimum And 2.448 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Bolt Tension Hex Head Close Tolerance Alloy Steel Short Thread Reduced Major Thread Dia. Self Locking And Non Locking 160 Ksi Ftu
Special Features:	Item Has Drilled Shank Bolt
Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6206-39> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.