



★ FASTENERS

[Military-Fasteners.com](http://Military-Fasteners.com)

**P/N NAS6206-48D**

## Description

length: 3.329", grip: 2.875", thread: 3/8-24, hex head, drilled shank, tension, short thread, cadmium plated alloy steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	NAS620648D
Minimum Qty (MOQ):	5
NSN:	5306-01-334-6321
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N NAS6206-48D Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.454 Inches Nominal
<b>Fastener Length:</b>	3.439 Inches Minimum And 3.469 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.188 Inches Minimum And 0.203 Inches Maximum
<b>Width Between Flats:</b>	0.559 Inches Nominal
<b>Grip Diameter:</b>	0.3735 Inches Minimum And 0.3745 Inches Maximum
<b>Shank Unthreaded Hole Diameter:</b>	0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole
<b>End Item Identification:</b>	Pacer Dawn
<b>Nominal Thread Diameter:</b>	0.3750 Inches
<b>Grip Length:</b>	2.090 Inches Minimum And 3.010 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	3.271 Inches Nominal First Hole
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6206-48D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.