

## **P/N NAS6207-28**

### **Description**

length: 2.278", grip: 1.750", thread: 7/16-20, hex head, tension, short thread, cadmium plated alloy steel

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS620728

Minimum Qty (MOQ): 5

NSN: 5306-01-114-5142

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









# **P/N NAS6207-28 Specifications**

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.503 Inches Minimum And 0.553 Inches Maximum
Fastener Length:	2.263 Inches Minimum And 2.293 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.219 Inches Minimum And 0.234 Inches Maximum
Width Between Flats:	0.678 Inches Minimum And 0.690 Inches Maximum
Grip Diameter:	0.4360 Inches Minimum And 0.4370 Inches Maximum
Nominal Thread Diameter:	0.438 Inches
Grip Length:	1.740 Inches Minimum And 1.760 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hardness Rating:	36.0 Rockwell C Minimum Overall And 40.0 Rockwell C Maximum Overall
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams6322 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6207 Professional/industrial Association Standard

## **How to Order**

Order this shear bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/shear+bolts/NAS6207-28">https://military-fasteners.com/bolts/shear+bolts/NAS6207-28</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/shear+bolts/NAS6207-28">https://military-fasteners.com/bolts/shear+bolts/NAS6207-28</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/shear+bolts/NAS6207-28">https://military-fasteners.com/bolts/shear+bolts/NAS6207-28</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="https://military-fasteners.com/bolts/shear+bolts/NAS6207-28">https://military-fasteners.com/bolts/shear+bolts/NAS6207-28</a> and selecting the quantity you want then