

Description

NAS6207-29D Shear Bolt

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS620729D
Minimum Qty (MOQ):	1
NSN:	5306-01-406-4181
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



NO IMAGE
AVAILABLE

P/N NAS6207-29D Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.528 Inches Nominal
Fastener Length:	2.325 Inches Minimum And 2.355 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.219 Inches Minimum And 0.234 Inches Maximum
Width Between Flats:	0.678 Inches Minimum And 0.690 Inches Maximum
Grip Diameter:	0.4360 Inches Minimum And 0.4370 Inches Maximum
Shank Unthreaded Hole Diameter:	0.106 Inches Minimum First Hole And 0.116 Inches Maximum First Hole
Nominal Thread Diameter:	0.4375 Inches
Grip Length:	1.802 Inches Minimum And 1.822 Inches Maximum
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	2.131 Inches Minimum First Hole And 2.151 Inches Maximum First Hole
Material:	Steel Comp E4340 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Mil-s-5000 Mil Spec 1st Material Response Overall Or Mil-s-6049 Mil Spec 2nd Material Response Overall Or Ams 6322 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall Or Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416, Ty2 Cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6207-29D> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.